






HEADROOM




OPENING HEIGHT =




NOTES:
1 - ALL FRAMES, JAMB EXTENSIONS & PADS TO BE SUPPLIED, INSTALLED PLUMB & SQUARE AND PROPERLY SUPPORTED BY OTHERS. ALL INSIDE FACES MUST BE FLUSH & BOLTHEADS COUNTERSUNK.
2 - ALL CLEARANCES AS SIDEROOM, HEADROOM AND DEPTH TO BE UNOBSTRUCTED.
3 - STEEL FRAMES MAY BE BUILT OF CHANNEL, ANGLES & PLATE OR ANGLE WITH INTERIOR FLANGE 3" WIDE MIN. FOR FASTENING DOOR TRACKS JAMB EXTENSIONS & PADS AS SHOWN TO RECEIVE COUNTERBALANCE MECHANISM.



A =



OPENING HEIGHT =



HIGH-LIFT

NOTES:
- ALL JAMB EXTENSIONS AND PADS TO BE SUPPLIED BY OTHERS.
- ALL ELECTRICAL WIRING (INCLUDING LOW VOLTAGE) BY OTHERS.

MODEL	QTY.	OPENING	CLEARANCE REQ'D			REQ'D DEPTH	GLAZED SECT.	GLASS
			A	B	C			
TRADITION MARK II - 244								

APPROVED FOR MANUFACTURING BY:
Name:.....
Signature:.....
Date:.....

THERMOSTOP INC.
3775 BOULEVARD LOSCH, ST-HUBERT, QUÉBEC J3Y 5T7

PROJECT NAME:
DISTRIBUTOR :
CONTRACTOR :
ARCHITECT :

DATE / /	DRAWN BY S.L.	VERIFIED BY	CONTRACT No.	DRAWING No. 2/2
----------	---------------	-------------	--------------	-----------------