







HEADROOM



OPENING HEIGHT =



NOTES:  
1 - ALL FRAMES, JAMB EXTENSIONS & PADS TO BE SUPPLIED, INSTALLED PLUMB & SQUARE AND PROPERLY SUPPORTED BY OTHERS. ALL INSIDE FACES MUST BE FLUSH & BOLTHEADS COUNTERSUNK.  
2 - ALL CLEARANCES AS SIDEROOM, HEADROOM AND DEPTH TO BE UNOBSTRUCTED.  
3 - STEEL FRAMES MAY BE BUILT OF CHANNEL, ANGLES & PLATE OR ANGLE WITH INTERIOR FLANGE 3" WIDE MIN. FOR FASTENING DOOR TRACKS JAMB EXTENSIONS & PADS AS SHOWN TO RECEIVE COUNTERBALANCE MECHANISM.



NOTES:  
- ALL JAMB EXTENSIONS AND PADS TO BE SUPPLIED BY OTHERS.  
- ALL ELECTRICAL WIRING (INCLUDING LOW VOLTAGE) BY OTHERS.

MODEL	QTY.	OPENING	CLEARANCE REQ'D			REQ'D DEPTH	GLAZED SECT.	GLASS
			A	B	C			
AL-2000								

APPROVED FOR MANUFACTURING BY:  
Name:.....  
Signature:.....  
Date:.....

**THERMOSTOP INC.**  
3775 BOULEVARD LOSCH, ST-HUBERT, QUÉBEC J3Y 5T7

PROJECT NAME:  
DISTRIBUTOR :  
CONTRACTOR :  
ARCHITECT :

DATE / /	DRAWN BY S.L.	VERIFIED BY	CONTRACT No.	DRAWING No. 2/2
----------	---------------	-------------	--------------	-----------------