

HEADROOM = A

OPENING HEIGHT =

75 EQ 325 EQ 75

NOTES:

1 - ALL FRAMES, JAMB EXTENSIONS & PADS TO BE SUPPLIED, INSTALLED PLUMB & SQUARE AND PROPERLY SUPPORTED BY OTHERS. ALL INSIDE FACES MUST BE FLUSH & BOLTHEADS COUNTERSUNK.

2 - ALL CLEARANCES AS SIDEROOM, HEADROOM AND DEPTH TO BE UNOBSTRUCTED.

3 - STEEL FRAMES MAY BE BUILT OF CHANNEL, ANGLES & PLATE OR ANGLE WITH INTERIOR FLANGE 3" WIDE MIN. FOR FASTENING DOOR TRACKS JAMB EXTENSIONS & PADS AS SHOWN TO RECEIVE COUNTERBALANCE MECHANISM.

B C

OPENING WIDTH =

REQUIRED DEPTH =

HEADROOM

OPENING HEIGHT =

INCLINED VERTICAL TRACKS FOR FREE RUNNING AND WEATHERTIGHT CLOSING

STEEL TRACK HANGERS TO SUIT JOB CONDITIONS BY DOOR ERECTOR

STANDARD ELEVATION

NOTES:

- ALL JAMB EXTENSIONS AND PADS TO BE SUPPLIED BY OTHERS.

- ALL ELECTRICAL WIRING (INCLUDING LOW VOLTAGE) BY OTHERS.

MODEL	QTY.	OPENING	CLEARANCE REQ'D			REQ'D DEPTH	GLAZED SECT.	GLASS
			A	B	C			
AL-2000								

APPROVED FOR MANUFACTURING BY:

Name:.....

Signature:.....

Date:.....

THERMOSTOP INC.

3775 BOULEVARD LOSCH, ST-HUBERT, QUÉBEC J3Y 5T7

PROJECT NAME:

DISTRIBUTOR :

CONTRACTOR :

ARCHITECT :

DATE / /

DRAWN BY S.L.

VERIFIED BY

CONTRACT No.

DRAWING No. 2/2