

HEADROOM = A

OPENING HEIGHT =

A = H.L. + (9" or 12") =

OPENING HEIGHT =

FACE FRAME 15"W x 1-1/2"thick

FACE FRAME 6"W x 1-1/2"thick

FACE FRAME 6"W x 1-1/2"thick

FACE FRAME 6"W x 1-1/2"thick

OPENING WIDTH =

REQUIRED DEPTH =

HI-LIFT =

INCLINED VERTICAL TRACKS FOR FREE RUNNING AND WEATHERTIGHT CLOSING

STEEL TRACK HANGERS TO SUIT JOB CONDITIONS BY DOOR ERECTOR

HIGH-LIFT

NOTES:

- ALL JAMB EXTENSIONS AND PADS TO BE SUPPLIED BY OTHERS.
- ALL ELECTRICAL WIRING (INCLUDING LOW VOLTAGE) BY OTHERS.

MODEL	QTY.	OPENING	CLEARANCE REQ'D			REQ'D DEPTH	GLAZED SECT.	GLASS
			A	B	C			

APPROVED FOR MANUFACTURING BY:

Name:.....

Signature:.....

Date:.....

**THERMOSTOP INC.**

3775 BOULEVARD LOSCH, ST-HUBERT, QUÉBEC J3Y 5T7

PROJECT :

DISTRIBUTOR :

CONTRACTOR :

ARCHITECT :

DATE	DRAWN BY S.L.	VERIFIED BY	CONTRACT No.	DRAWING No. 2/2
------	------------------	-------------	--------------	--------------------