

HEADROOM = A

OPENING HEIGHT =

A = H.L. + (9" or 12") =

OPENING HEIGHT =

FACE FRAME
15"W x 1-1/2"thick

FACE FRAME
6"W x 1-1/2"thick

FACE FRAME
6"W x 1-1/2"thick

FACE FRAME
6"W x 1-1/2"thick

OPENING WIDTH =

REQUIRED DEPTH =

STEEL TRACK HANGERS TO
SUIT JOB CONDITIONS BY
DOOR ERECTOR

HI-LIFT =

INCLINED VERTICAL TRACKS FOR FREE
RUNNING AND WEATHERTIGHT CLOSING

FACE FRAME

HIGH-LIFT

NOTES:

ALL FRAMES ARE SUPPLY BY THERMOSTOP,
INSTALED PLUMB & SQUARE AND PROPEALY
SUPPORTED BY OTHERS. ALL INSIDE FACES MUST
BE FLUSH & BOLTHEADS COUNTERSUNK.

ALL CLEARANCES AS SIDEROOM, HEADROOM AND
DEPTH TO BE UNOBSTRUCTED.

MODEL	QTY.	OPENING	CLEARANCE REQ'D			REQ'D DEPTH	GLAZED SECT.	GLASS
			A	B	C			
21-266								

APPROVED FOR MANUFACTURING BY:

Name:.....

Signature:.....

Date:.....

THERMOSTOP INC.

3775 BOULEVARD LOSCH, ST-HUBERT, QUÉBEC J3Y 5T7

PROJECT :

DISTRIBUTOR :

CONTRACTOR :

ARCHITECT :

DATE	DRAWN BY P.B.	VERIFIED BY	CONTRACT No.	DRAWING No. 2/2
------	------------------	-------------	--------------	--------------------